Citronix

ct2000 Series

Thermal Inkjet Printer

The ct2000 Series provides a reliable, maintenance-free Thermal Inkjet solution for high-performance industrial printing.

Capable of printing high-resolution graphics and codes at high speeds, the ct2000 Series works with a wide range of water and solvent-based inks, making it ideal for a range of industries and applications such as food & beverage, pharmaceutical and industrial. Designed for zero maintenance, high reliability, and fast cartridge changeovers, the ct2000 Series helps customers save both time and money.



Intuitive user interface



Remote printing



Maintenance free



Up to 4" print height



Graphic 1D/2D codes up to 600dpi



High speed printing up to 228 m/min



Simple



The ct2000 Series simplifies printing tasks with its intuitive operation. Featuring an easy-to-use touchscreen interface up to 10 inches, along with remote web access, it provides a seamless and user-friendly experience.

Reliable



Standing out for its reliability, with a 24-month warranty and robust construction using stainless steel, anodized aluminum, and toughened glass, the ct2000 Series ensures durability in demanding environments.



Excellent Value



Delivering the right capabilities at the right price, the series offers excellent value, with products to suit a wide range of applications. Its durable, maintenance-free design ensures cost-effective and reliable performance.



Capable



Powerful electronics and advanced software ensures the ct2000 Series is equipped to handle the most demanding applications. It supports a variety of printhead technologies and ink cartridges, both water- and solvent-based, capable of printing heights of up to 4 inches in high resolution.

Technical Specifications











Features	ct2030-S & ct2030-H	ct2050-S & ct2050-H	ct2200	ct2400
Display	-	3.5" LCD Display	7" capacitive touchscreen	10" capacitive touchscreen
Keyboard	-	•	-	-
Browser access	•	•	•	•
Supported languages	Includes English, German, Vietnamese, Korean, Russian, Simplified Chinese, Turkish, Portuguese, Spanish, Polish, and many more			
Bracketry	Bracketry included	Bracketry included	Bracketry purchased separately	Bracketry purchased separately
Dimensions (L x W x H)	120.6 x 86.1 x 90 mm	120.6 x 86.1 x 90 mm	242 x 158 x 58 mm	320 x 208 x 56 mm
Printhead	Integrated	Integrated	Up to 2 printheads	Up to 4 printheads
Printhead type	ct2030-S> S-Head ct2030-H> H-Head	ct2050-S> S-Head ct2050-H> H-Head	S-, H- & T-Heads available separately	S-, H- & T-Heads available separately
Maximum print height	1"	1"	2"	4"
Photocell	1x inbuilt, 1x external	1x inbuilt, 1x external	1x external	1x external
Alarm beacon outputs	3	3	3	3
Spare digital I/O	1 input, 1 output	1 input, 1 output	1 input, 1 output	1 input, 1 output
TCP/IP	•	•	•	•
USB ports	2	2	2	1
RS232/RS485 ports	RS485	RS485	RS232	RS232
Pro upgrade available*	•	•	•	•
Power supply	100-240VAC	100-240VAC	100-240VAC	100-240VAC

Print Heads

Construction

Print height

Print speed

Throw distance

Max resolution

S-Head (Standard)



Stainless Steel 1mm to 3 mm 600dpi x 600dpi

Dimensions (excluding cartridge) Typical cartridge volume Smart chip

42ml

135 x 46 x 58mm

133 x 65 x 84mm

Print speed up to 456m/min @ 300dpi x 100dpi

H-Head (1" print Height)



Construction Stainless Steel Print height Throw distance 1mm to 3 mm

Print speed

Max resolution 300dpi x 600dpi

Dimensions (excluding cartridge)

* Pro upgrade adds database and remote communications capability.

Typical cartridge volume Smart chip

135 x 44 x 71mm 40ml

up to 456m/min @ 300dpi x 100dpi

T-Head (Long Throw distance)



Construction Stainless Steel Print height 0.5" Throw distance 1mm to 12 mm Max resolution 300dpi x 600dpi

Dimensions (excluding cartridge) Typical cartridge volume Smart chip

40ml Yes

up to 121m/min @ 300dpi x 100dpi

Print Capability

